



### Dimension

Unit:mm

Model	D	I	L	E	F	G	H	M	d1xd2 (H7)		Mass** Weight (g)
									Min	Max	
SRJ-20C-RD	20	10	30	9	0.5	5.0	6.5	M2.5	5	8	19
SRJ-30C-RD	30	11	34	11	0.5	5.5	10.0	M4	6	14	50
SRJ-40C-RD	40	25	66	14	1.0	8.5	14.0	M5	10	19	190
SRJ-55C-RD	55	30	78	16	1.0	10.5	20.0	M6	15	25	412
SRJ-65C-RD	65	35	90	17.5	1.25	13.0	24.0	M8	12	35	560
SRJ-80C-RD	80	45	114	21	1.5	15.0	31.0	M8	15	45	1400

### Specifications

Unit:mm

Model	Rated Torque (N.m)	Max. Torque (N.m)	Max Rotational Frequency (Rpm/min)	Moment* of Inertia (Kg · m <sup>2</sup> )	Errors of Eccentricity (mm)	Errors of Angularity (°)	Errors of Shaft End-Play (mm)
SRJ-20C-RD	5.0	10	23000	1.0x10 <sup>-6</sup>	0.10	1.0	± 0.4
SRJ-30C-RD	12.5	25	19000	6.1x10 <sup>-6</sup>	0.10	1.0	± 0.5
SRJ-40C-RD	17.0	34	14000	3.8x10 <sup>-5</sup>	0.10	1.0	± 0.6
SRJ-55C-RD	60.0	120	10500	1.5x10 <sup>-4</sup>	0.10	1.0	± 0.7
SRJ-65C-RD	160.0	320	8500	3.8x10 <sup>-4</sup>	0.10	1.0	± 0.75
SRJ-80C-RD	450.0	900	7100	6.2x10 <sup>-3</sup>	0.10	1.0	+ 0.8